

Indoor unit model name SRK25ZSX-W Outdoor unit model name SRC25ZSX-WA

Refrigerant	R32	GWP		675
Temperant	NJZ	UWF		
contribute less to appliance contai would be leaked over a period of	o global warming than ns a refrigerant fluid w to the atmosphere, th	a refrigerant vith a GWP e e impact on o interfere w	t with I equal to global	perant with lower global warming potential (GWP) would higher GWP, if leaked to the atmosphere. This o 675. This means that if 1kg of this refrigerant fluid warming would be 675 times higher than 1kg of CO2, refrigerant circuit yourself or disassemble the product
Cooling mode				
SEER		10.3		
Energy efficie		A+++		
Design load (kW	
Energy consu				per year.based on standard test results.
Actual effer	gy consumption will	depend on	now	the appliance is used and where it is located.
Heating mode (A	verage)			
SCOP	0,	5.2		
Energy efficie	ency class	A+++		
Design load (Pdesignh)		kW	(-10°C)
Declared cap		3.00		(-10°C)
Back up heat			kW	(-10°C)
Energy consu				per year.based on standard test results.
Actual ener	gy consumption will	depend on	now	the appliance is used and where it is located.
Heating mode (V	Varmer) Optional			
SCOP	ranner, epitenar	6.6		
Energy efficie	encv class	A+++		
Design load (4.2	kW	(2°C)
Declared cap		4.20		(2°C)
Back up heat			kW	(2°C)
Energy consu		891	kWh	per year based on standard test results.
Actual ener	gy consumption will	depend on	how	the appliance is used and where it is located.
Heating mode (0	Joider) Optional			
SCOP		-		
Energy efficie		-		(22°C)
Design load (kW kW	(-22°C)
Declared cap	3		кvv kW	(-22°C)
Back up heat Energy consu				(-22°C) per year.based on standard test results.
				the appliance is used and where it is located.
	gy consumption will		100	and appliance is about and where it is located.
Sound power	level (indoor)	55		dB(A)
	level (outdoor)	57		dB(A)